



# Ladder Guard

Data Sheet v1.0



CableSafe® / Westmark B.V.  
Arnhemseweg 87, 3832 GK Leusden



+31334614844



[info@cablesafe.com](mailto:info@cablesafe.com)

# Confined Space Safety Ladder Guard

## Description

CableSafe Ladder Guard is used to prevent unauthorized access to a ladder. The Ladder Guard restricts unauthorised ladder access on site and is an important safety measure. CableSafe Ladder Guard provides a quick and easy solution: hooking over the rung of the ladder and can be locked at the front or the rear through the stainless steel padlock bracket (padlocks supplied optional). Fits ladders with an internal rung width of 250mm – 450mm.



## Technical Data

- **Standard Size:** 1800mm x 450mm (cut to size free of charge)
- **Thickness:** 6mm
- **Material:** Glass reinforced polyester (GRP)
- **Suitable Environments:** Internal, external, commercial and industrial
- **Applications:** Ladders
- **Fixing Method:** Hook over at top. Padlock to bottom (optional)

MODEL	CHARACTERISTICS
<b>Ladder Guard</b>	<ul style="list-style-type: none"> <li>• Easily handled and installed by one person.</li> <li>• Quick and simple to install / remove from almost any ladder size.</li> <li>• Last well over 20 years.</li> <li>• Weight is 9 kg at 1800 mm x 380 mm wide</li> <li>• 'Caution, Do not climb' label included on all Ladder Guards.</li> <li>• Ladder Guards can be cut to your exact requirement free of charge.</li> <li>• Padlock bracket included.</li> <li>• Padlock supplied optional.</li> </ul>

# Confined Space Safety Ladder Guard

## Pictures



> Ladder Guard Installed



> Hook over at top



> Padlock



> Padlock bracket



> Complete ladder guard

# OUR WORK AREA



CableSafe® / Westmark  
B.V Arnhemseweg 87  
3832 GK Leusden

